

Important Notice: The manufacturer and the seller warrant the chemical contained in this bottle conforms to standard specifications. Sellers and manufacturers liability for any and all losses or damages associated with this product shall in no case exceed the purchase price of this product. Before using, user shall determine suitability of this product for the intended purpose and assume all risks associated with its use. Go Clean Supply P.O. Box 14016 Las Vegas, Nevada 89114 866-839-7588 www.gocleansupply.com

Heavy Duty Fabric Pre-spray is a blend of emulsifiers, solvents and ammonia for fast action on heavily soiled fabrics

Directions:

1. Vacuum fabric thoroughly before starting cleaning process.
2. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
3. For light to medium soil, mix one part Heavy Duty Fabric Pre-spray with three parts water (42 ounces of solution with gallon of water) into sprayer. For heavy soiling, do not dilute. Use straight.
4. Apply with hand-held pump up or trigger sprayer in an even, overlapping mist across the entire area of the fabric being cleaned.
5. Allow to dwell for 2-3 minutes. Be careful not to overspray or breathe mist.
6. Agitate with horsehair brush or bonnet mitt.
7. For best results extract area with Final Rinse using an Upholstery Cleaning Tool.
8. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

CAUTION: May affect the central nervous system causing dizziness, headache, or nausea. May be harmful if inhaled. May be harmful if swallowed. For more information, refer to MSDS.

Contains: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).



Heavy Duty Fabric Pre-Spray

GO CLEAN™

Tela Heavy Duty Pre-aerosol es una mezcla de emulsionantes, disolventes y amoníaco para la acción rápida en telas muy sucias

Instrucciones:

1. Tela de vacío a fondo antes de comenzar el proceso de limpieza.
2. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
3. Para suciedad leve y mediano, mezcle una parte pesada tela deber Pre-spray con tres partes de agua (42 onzas de solución con un galón de agua) en el pulverizador. Si están muy sucios, no lo diluya. Utilice recta.
4. Aplicar con la bomba de mano hacia arriba o desencadenar pulverizador en una niebla aún, la superposición en toda el área de la tela que se limpia.
5. Dejar reposar durante 2-3 minutos. Tenga cuidado de no respirar exceso de pulverización o neblina.
6. Agite con un cepillo de crin o el capó guante.
7. Para obtener los mejores resultados extraer área con enjuague final con una herramienta de limpieza de la tapicería.
8. Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un motor de aire centrífugo o axial corriente descendente después de la limpieza.

Precaución: Puede afectar al sistema nervioso central que causa mareos, dolor de cabeza o náuseas. Puede ser nocivo si se inhala. Puede ser nocivo si se ingiere. Para obtener más información, consulte la MSDS.

Contiene: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).

NET CONTENTS: 1 Quart

NOT FOR RESALE

PRODUCT HAS BEEN DILUTED AS DIRECTED ON PRIMARY LABEL

Important Notice: The manufacturer and the seller warrant the chemical contained in this bottle conforms to standard specifications. Sellers and manufacturers liability for any and all losses or damages associated with this product shall in no case exceed the purchase price of this product. Before using, user shall determine suitability of this product for the intended purpose and assume all risks associated with its use. Go Clean Supply P.O. Box 14016 Las Vegas, Nevada 89114 866-839-7588 www.gocleansupply.com

Heavy Duty Fabric Pre-spray is a blend of emulsifiers, solvents and ammonia for fast action on heavily soiled fabrics

Directions:

1. Vacuum fabric thoroughly before starting cleaning process.
2. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
3. For light to medium soil, mix one part Heavy Duty Fabric Pre-spray with three parts water (42 ounces of solution with gallon of water) into sprayer. For heavy soiling, do not dilute. Use straight.
4. Apply with hand-held pump up or trigger sprayer in an even, overlapping mist across the entire area of the fabric being cleaned.
5. Allow to dwell for 2-3 minutes. Be careful not to overspray or breathe mist.
6. Agitate with horsehair brush or bonnet mitt.
7. For best results extract area with Final Rinse using an Upholstery Cleaning Tool.
8. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

CAUTION: May affect the central nervous system causing dizziness, headache, or nausea. May be harmful if inhaled. May be harmful if swallowed. For more information, refer to MSDS.

Contains: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).



Heavy Duty Fabric Pre-Spray

GO CLEAN™

Tela Heavy Duty Pre-aerosol es una mezcla de emulsionantes, disolventes y amoníaco para la acción rápida en telas muy sucias

Instrucciones:

1. Tela de vacío a fondo antes de comenzar el proceso de limpieza.
2. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
3. Para suciedad leve y mediano, mezcle una parte pesada tela deber Pre-spray con tres partes de agua (42 onzas de solución con un galón de agua) en el pulverizador. Si están muy sucios, no lo diluya. Utilice recta.
4. Aplicar con la bomba de mano hacia arriba o desencadenar pulverizador en una niebla aún, la superposición en toda el área de la tela que se limpia.
5. Dejar reposar durante 2-3 minutos. Tenga cuidado de no respirar exceso de pulverización o neblina.
6. Agite con un cepillo de crin o el capó guante.
7. Para obtener los mejores resultados extraer área con enjuague final con una herramienta de limpieza de la tapicería.
8. Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un motor de aire centrífugo o axial corriente descendente después de la limpieza.

Precaución: Puede afectar al sistema nervioso central que causa mareos, dolor de cabeza o náuseas. Puede ser nocivo si se inhala. Puede ser nocivo si se ingiere. Para obtener más información, consulte la MSDS.

Contiene: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).

NET CONTENTS: 1 Quart

NOT FOR RESALE

PRODUCT HAS BEEN DILUTED AS DIRECTED ON PRIMARY LABEL

Important Notice: The manufacturer and the seller warrant the chemical contained in this bottle conforms to standard specifications. Sellers and manufacturers liability for any and all losses or damages associated with this product shall in no case exceed the purchase price of this product. Before using, user shall determine suitability of this product for the intended purpose and assume all risks associated with its use. Go Clean Supply P.O. Box 14016 Las Vegas, Nevada 89114 866-839-7588 www.gocleansupply.com

Heavy Duty Fabric Pre-spray is a blend of emulsifiers, solvents and ammonia for fast action on heavily soiled fabrics

Directions:

1. Vacuum fabric thoroughly before starting cleaning process.
2. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
3. For light to medium soil, mix one part Heavy Duty Fabric Pre-spray with three parts water (42 ounces of solution with gallon of water) into sprayer. For heavy soiling, do not dilute. Use straight.
4. Apply with hand-held pump up or trigger sprayer in an even, overlapping mist across the entire area of the fabric being cleaned.
5. Allow to dwell for 2-3 minutes. Be careful not to overspray or breathe mist.
6. Agitate with horsehair brush or bonnet mitt.
7. For best results extract area with Final Rinse using an Upholstery Cleaning Tool.
8. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

CAUTION: May affect the central nervous system causing dizziness, headache, or nausea. May be harmful if inhaled. May be harmful if swallowed. For more information, refer to MSDS.

Contains: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).



Heavy Duty Fabric Pre-Spray

GO CLEAN™

Tela Heavy Duty Pre-aerosol es una mezcla de emulsionantes, disolventes y amoníaco para la acción rápida en telas muy sucias

Instrucciones:

1. Tela de vacío a fondo antes de comenzar el proceso de limpieza.
2. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
3. Para suciedad leve y mediano, mezcle una parte pesada tela deber Pre-spray con tres partes de agua (42 onzas de solución con un galón de agua) en el pulverizador. Si están muy sucios, no lo diluya. Utilice recta.
4. Aplicar con la bomba de mano hacia arriba o desencadenar pulverizador en una niebla aún, la superposición en toda el área de la tela que se limpia.
5. Dejar reposar durante 2-3 minutos. Tenga cuidado de no respirar exceso de pulverización o neblina.
6. Agite con un cepillo de crin o el capó guante.
7. Para obtener los mejores resultados extraer área con enjuague final con una herramienta de limpieza de la tapicería.
8. Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un motor de aire centrífugo o axial corriente descendente después de la limpieza.

Precaución: Puede afectar al sistema nervioso central que causa mareos, dolor de cabeza o náuseas. Puede ser nocivo si se inhala. Puede ser nocivo si se ingiere. Para obtener más información, consulte la MSDS.

Contiene: Propanol (CAS 67-63-1), Glycol Ether (CAS #111-76-2), and Nonylphenol Ethoxylated (CAS #9016-45-9).

NET CONTENTS: 1 Quart

NOT FOR RESALE

PRODUCT HAS BEEN DILUTED AS DIRECTED ON PRIMARY LABEL